

## Subrack 14 – 19“ Subrack, 14 Slots for 6U cPCI Boards, Height 6U



### Features

- Designed for IO intensive HIL systems
- 14/18/21 6U cPCI slots
- Usable for up to 80 IO modules
- Vertical card mounting orientation
- Rear IO (optional)
- EMC protected

### Technical Data

Number of IO modules	Up to 80 IO-modules
cPCI backplane	6U, up to 21 slots, 64bit
RearIO	Optional
cPCI IO voltage	<ul style="list-style-type: none"> <li>• 3,3V</li> <li>• 5V (optional)</li> </ul>
Card mounting orientation	Vertical
Power supply	<ul style="list-style-type: none"> <li>• 400W cPCI power supply with active PFC</li> <li>• Input: <ul style="list-style-type: none"> <li>• 100..240V, 50/60Hz, max 5Amps</li> </ul> </li> <li>• Output: <ul style="list-style-type: none"> <li>• 3,3V / 35A</li> <li>• 5V / 60A</li> <li>• 12V / 14A</li> </ul> </li> </ul>
Heat dissipation	From the lower front side to the rear side with fans
Dimensions (WxHxD)	483x311x355mm (without handles)

### Order Information

Order Number	SR19-14	On request
Scope of Delivery	Subrack, rack mounting kit, power cord (region specific), Rear IO slots covered - covers for empty front slots on request	19“ Subrack 6U 18/21 Slots