

## Subrack 5 – 19“ Subrack, 5 Slots for 6U cPCI Boards, Height 3U



### Features

- 5x 6U cPCI slots
- Height 3U
- Usable for up to 16 IO modules
- Rear IO
- High quality, silent 12cm fan
- Horizontal card mounting orientation
- Desktop subrack available (optional)

### Technical Data

Number of IO modules	Up to 16 IO-modules
cPCI backplane	6U, 5 slots, 64bit rear IO
cPCI IO voltage	<ul style="list-style-type: none"> <li>• 3,3V</li> <li>• 5V (optional)</li> </ul>
Card mounting orientation	Horizontal
Power supply	<ul style="list-style-type: none"> <li>• 300W ATX power supply with active PFC</li> <li>• Input: 90..264V, 50/60Hz, 6A/3A (115V/230V)</li> <li>• Output: <ul style="list-style-type: none"> <li>• 3,3V / 28A</li> <li>• 5V / 35A</li> <li>• 12V / 22A</li> <li>• (5V + 3,3V together: max 45A)</li> </ul> </li> </ul>
Heat dissipation	From the right front panel to the left side with one 12cm fan
Dimensions (WxHxD)	483x131x297mm (without handles)

### Order Information

Order Number	SR19-5	DC19-3U
Scope of Delivery	Subrack, rack mounting kit, power cord (region specific), Rear IO slots covered - ask for front slot covers matching your configuration	Desktop Stand